

P-touch

PT-P900W / PT-P950NW

brother
at your side



Professional Network Label Printer Series

Print durable labels from PC, Mac OS® systems and smart devices using wireless or wired* network connectivity.

- Create durable labels up to 36mm in width
- High speed and high resolution printing
- Wired* network and Wireless network connectivity
- Advanced half cut function with easy label peel feature
- Print images, barcodes and frames on labels
- Connect to imported database to print many labels
- Software development kits (SDK) available for Windows, iOS and Android devices

*PT-P950NW only



Offering the highest print speed and print resolution, PT-P900 professional label printers series, can produce durable labels up to 36mm in width.

Print text, barcodes, images and logos on durable TZe laminated that are suitable for indoor or outdoor use that will last for many years.

Choose between wireless and wired network connectivity and a range of optional accessories to create a customised label printing solution.

P-touch



Key features at a glance

	PT-P900W	PT-P950NW
Print durable labels from 3.5mm to 36mm in width	●	●
Large 32mm print height for near edge-to-edge printing	●	●
360dpi print resolution for crisp text, images and barcodes	●	●
High speed printing of up to 60mm per second	●	●
USB and Wi-Fi connectivity	●	●
Wired network connectivity (10/100 Base-TX LAN)		●
Advanced half cut function that can print easy-peel labels in a continuous strip for easy labels management	●	●
Use the free professional desktop P-touch Editor label design software	●	●
Software development kits (SDK) available to easily add label printing to third party software or apps	●	●
Merge text contained in Excel, .csv and MSDE/SQL databases to easily print many labels	●	●
Print 1D and 2D industry standard barcodes	●	●
Free iOS or Android label apps to print labels from smart devices	●	●
Optional Rechargeable Li-ion battery and battery base	●	●
Optional RJ25 to DB9M serial adapter	●	●
Optional Bluetooth interface		●
Optional Touch Panel with backlit LCD display to print custom labels without the use of a PC including current or future time and date		●



Professional label printers designed for any labelling task.

With a wide range of tapes colours and tape widths up to 36mm and near to almost borderless printing with high speed and high resolution print capabilities, these label printers are ideal for facilities management, document archiving, asset labelling and print labels on-demand.

Wired, Wireless network and Bluetooth connectivity.

These compact desktop label printers can connect to PC or Mac OS® systems using USB or Wireless network connections. PT-P950NW can connect to wired network or an optional Bluetooth module that allows easy connection directly to smart devices, PC and Bluetooth input devices such as barcode scanners.



Industrial label design software

Both models use the free P-touch Editor label design software for Windows and Mac OS® systems. Create 1D and 2D barcodes, import of logos and any other graphics using P-touch Editor label design software. Link to a Microsoft Excel® spreadsheet or .csv file to print multiple labels quickly and efficiently.



Print from smart devices.

Instantly create and print simple labels from smart devices without the need of a PC. Brother iPrint&Label app allows wireless connection to the printer to design and print labels from iOS or Android devices. Identify any electrical and datacom cabling and equipment by using Brother Cable Label Tool app to print labels for wrapping around cables or faceplates, electrical distribution boards and other specialist equipment.

Software Development Kit (SDK)

Software and app developers can use the various Software development kits (SDK) for Microsoft Windows, iOS and Android devices to enable label printing from third party software and apps. This makes these printers ideal to integrate into any customized solutions.



Advanced half cut function with easy-peel feature.

The advanced half cut function can produce one long strip of labels that can be easily peeled one-at-a-time and ensure labels are kept in the correct order. Alternatively, label can be fully cut as well if required.





Print from anywhere.

There are situations where AC Power adapter may not be available, such as on construction sites or when the label printer is on a portable trolley. Attach the optional Rechargeable Li-ion battery and battery base to enable label printing wherever and whenever required.

Print on demand without connecting to PC.

Ideal for the food, healthcare and laboratory industry, the optional PA-TDU-003 Touch Panel Display Unit (for PT-P950NW) allow printing of labels without PC connection. Design label and upload to the required location indicated on the buttons, the user can simply press the relevant button to print labels on demand. The built-in clock allow labels to be printed with current and future Use by time and dates.



Optional accessories



PA-BB-002

Battery base for Rechargeable Li-ion battery



PA-BT-4000LI

Rechargeable Li-ion battery



PA-SCA-001

RJ25 to DB9M serial adapter



PA-BI-002

Bluetooth interface (For PT-P950NW only)



PA-TDU-003

Touch Panel display for stand-alone label print (For PT-P950NW only)

TZe laminated labels – designed to last

Brother TZe laminated tapes consist of six layers of materials, resulting in a thin yet extremely strong label.

Tested to the extreme

The direct thermal transfer ink is sandwiched between two protective layers of PET (polyester film) which protects the text against the effects of liquids, abrasion, temperature, chemicals and sunlight. As the labels are tested to the extreme, professional quality labels have been designed to last.



Temperature resistant: laminated labels were subjected to temperatures ranging from -80°C to +150°C for 240 hours and the text was unaffected.



Fade resistant: After laminated labels were placed in a fade-inducing chamber to simulate a year in sunny surroundings, the text was unaffected.



Water and chemical resistant: Glass plates with laminated labels attached were immersed in water and various chemicals for 2 hours. The text was unaffected.



Abrasion resistant: After 1kg of sanding device was passed over the laminated labels for 50 times, the text was unaffected.



Laminated



Temperature Resistant



Water Resistant



Fade Resistant



Abrasion Resistant



Chemical Resistant



Easy Peel



Strong Adhesive

TZe Tape range

3.5mm	6mm	9mm	12mm	18mm	24mm	36mm
Standard Laminated tape (8m or *4m long)						
	TZe-111	TZe-121	TZe-131	TZe-141	TZe-151	TZe-161
			TZe-132			
			TZe-133			
			TZe-135			
	TZe-211	TZe-221	TZe-231 / 231S*	TZe-241	TZe-251	TZe-261
		TZe-222	TZe-232	TZe-242	TZe-252	TZe-262
		TZe-223	TZe-233	TZe-243	TZe-253	TZe-263
			TZe-334	TZe-344	TZe-354	
	TZe-315	TZe-325	TZe-335	TZe-345	TZe-355	TZe-365
		TZe-421	TZe-431	TZe-441	TZe-451	TZe-461
			TZe-435			
		TZe-521	TZe-531	TZe-541	TZe-551	TZe-561
			TZe-535		TZe-555	
	TZe-611	TZe-621	TZe-631	TZe-641	TZe-651	TZe-661
		TZe-721	TZe-731	TZe-741	TZe-751	
Fluorescent Laminated tapes - 5m long						
			TZe-B31		TZe-B51	
			TZe-C31		TZe-C51	
Matt Laminated tapes - 8m or **5m long						
			TZe-M31			
			TZe-MQL35**			
			TZe-MQP35**			
			TZe-MQG35**			
Metallic Laminated tapes - 8m long						
		TZe-M921	TZe-M931		TZe-M951	TZe-M961
Non Laminated tapes - 8m long						
TZe-N201		TZe-N221	TZe-N231	TZe-N241	TZe-N251	
Flexi-ID Laminated tapes - 8m long						
	TZe-FX211	TZe-FX221	TZe-FX231	TZe-FX241	TZe-FX251	TZe-FX261
	TZe-FX611	TZe-FX621	TZe-FX631	TZe-FX641	TZe-FX651	TZe-FX661
Strong Adhesive Laminated tapes - 8m long						
		TZe-S121	TZe-S131	TZe-S141	TZe-S151	
	TZe-S211	TZe-S221	TZe-S231	TZe-S241	TZe-S251	TZe-S261
		TZe-S621	TZe-S631	TZe-S641	TZe-S651	
Fabric tapes - 3m long						
			TZe-FA3			
			TZe-FAE3			
			TZe-FA53			
			TZe-FA63			
Security Laminated tapes - 8m long						
				TZe-SE4	TZe-SE5	

HSe heat shrink tube range (1.5m long)

5.8mm	8.8mm	11.7mm	17.7mm	23.6mm
HSe-211	HSe-221	HSe-231	HSe-241	HSe-251

FLe die-cut label range (72 labels)

21mm x 45mm
FLe-2511
FLe-6511
FLe-7511

Tapes availability differ by different countries.



Specification

Label printing

Print labels up to 36mm in width
Maximum print height of 32mm for near edge-to-edge printing
360dpi print resolution for crisp, legible text, images and barcodes
Fast print speed at 60mm per second
Built-in automatic label cutter with easy-peel function
Minimum label length: 4mm | Maximum label length: 1m
Print up to 17 lines per label
Number of copies: 1 - 999

Connectivity: Wired Network

USB: Windows® (USB1.1, 2.0, 3.0 protocol) | Mac OS® systems (USB 1.0, 2.0 protocol)
Wired Network: 10 Base-T/100 Base-TX (For PT-P950NW only)
Serial: RS-232C (For printing with ESC/P commands only. Requires an optional serial adapter.)

Connectivity: Wireless Network

Wireless Direct: IEEE 802.11n | Ad-Hoc mode: IEEE802.11b | Infrastructure mode: IEEE802.11b/g/n | WPS 2.0

Connectivity: Bluetooth (Optional accessory to purchase for PT-P950NW)

Bluetooth 2.1+EDR | Profiles: SPP, OPP

Printer emulations and printer modes

P-touch Raster | ESC/P | P-touch Template

Label creation (PC or Mac® OS systems)

Uses P-touch Editor label design software
Link to data stored in Microsoft® Excel® (Windows®) and .csv (Mac) files, to merge onto labels
Choose any fonts installed on PC or Mac OS® systems to fully customise label
Support popular image formats (.bmp, .dib, .jpg, .tif, .ico, .wmf)
Special cable labelling wizard to easily create labels for cables, patch panels, faceplates and switches
Use date and time stamping to automatically include current or future dates and time on labels

Barcode protocols supported

1D: CODE39, CODE128, ITF 2/5, EAN13, EAN8, UPC-A, UPC-E, CODABAR, GS1-128 (UCC/EAN128)
2D: QR Code, PDF417, Data Matrix, Aztec Code, RSS-14 (Standard, Truncated, Stacked, StackedOmni), RSS-Limited, RSS Expanded (Standard, Stacked)

Dimension and Weight

118mm (W) x 192mm (D) x 146mm (H) | 1.48kg (PT-P900W) / 1.51kg (PT-P950NW)

Package content

TZe-261 36mm Black on White tape (8m long)
AD-9100ESA AC Power adapter
USB cable
User guide

Tape types supported

TZe tape: 3.5mm - 36mm
HSe heat shrink tube: 5.8mm - 23.6mm
FLe die-cut labels: 21mm x 45mm

System Requirements

Operating Systems: Microsoft® Windows Vista® | Microsoft® Windows® 7 | Microsoft® Windows® 8 | Microsoft® Windows® 8.1
Microsoft® Windows® 10 | Microsoft® Windows Server® 2008 | Microsoft® Windows Server® 2008 R2 | Microsoft® Windows Server® 2012
Microsoft® Windows Server® 2012 R2 | Mac OS X 10.9.5/10.10.x/10.11.x

Hard disk space: Windows®: More than 70MB | Mac: More than 500MB

System memory: As per operating system requirements

Microsoft® Office® support for P-touch add-in:

Microsoft® Word 2007/2010/2013/2016 | Microsoft® Excel® 2007/2010/2013/2016 | Microsoft® Outlook® 2007/2010/2013/2016

Microsoft, Windows, Windows Server and Windows Vista are registered trademarks or trademarks of Microsoft Corporation in United States or other countries. Apple, Mac, Mac OS, iPhone, iPad and iPod touch are trademarks of Apple Inc., registered in United States and other countries.

All specifications are correct at the time of printing. Brother is a registered trademark of Brother Industries Ltd.
Brand product names are registered trademarks or trademarks of their respective companies. Label images shown are for illustrative purposes only and some aspects may not be reproducible on these models. Product specifications may be subjected to change.